

HEAVY  
DUTY

# Dura-Flex Pro



- Heavy Duty, .160 Wall Thickness
- ISO 6945 Certified
- Professional Grade Construction
- Smooth Inner Wall Prevents Internal Abrasion Damage
- Braided Nylon Resists UV, Salt, Chemicals, Vermin and Rot

## ISO 6945 Certified Hose Protection

Dura Flex Professional (DP) provides tough hose protection two ways. First, per the ISO 6945 spec, DP's unique .160 thick tubular weave design will withstand greater than 200,000 abrasion cycles without wearing through the fabric at any location.

Additionally, the exceptionally smooth inner wall provides easy installation and minimizes any internal abrasion problems.

The tightly woven Nylon® construction is extremely flexible and resists chemical and ultraviolet degradation.

Dura-Flex Professional cuts with a scissor, installs quickly and easily.

DP is perfect for industrial and construction applications where ISO certified hose protection is called for.



Whatever your hose or application, DP will provide an extra level of protection from cuts, abrasion and UV damage.



Inside Diameter	Part #	Expansion Range		Bulk Lengths	Minimum Cuts	Available Colors	Lbs/100'
		Min.	Max.				
.75"	DPN0.75	This is a non-expandable product. Be sure to match your application diameter accurately.		100'	50'	Our standard, in-house color is Black. Custom colors are available per the adjacent color chart. Ask your Account Rep for details.	4.43
.93"	DPN0.93			100'	50'		5.51
1.13"	DPN1.13			100'	50'		7.15
1.22"	DPN1.22			100'	50'		7.44
1.35"	DPN1.35			100'	50'		8.02
1.43"	DPN1.43			100'	50'		8.32
1.63"	DPN1.63			100'	50'		9.53
1.81"	DPN1.81			100'	50'		10.71
2.19"	DPN2.19			100'	50'		12.31
2.63"	DPN2.63			100'	50'		14.83
2.88"	DPN2.88	100'	50'	17.30			
3.13"	DPN3.13	50'	25'	18.04			
3.38"	DPN3.38	50'	25'	20.11			
3.63"	DPN3.63	50'	25'	21.60			
4.00"	DPN4.00	50'	25'	23.52			

800 323-5140  
www.techflex.com