

# An Ideal Sleeving For Projects When A Hot Knife Is Inaccessible

FLEXO® FR PLUS (FRP) sleeving for electronic and high-tech applications incorporates the specialized resin coating and fray-resistance of FLEXO® PET Plus with the added benefit of flame retardant protection. It cuts easily and cleanly with ordinary scissors, making FLEXO® FR Plus ideal for projects when a hot knife is inaccessible. It has a wide operating temperature range resistant to chemical degradation, UV radiation and abrasion. Its organic combustion inhibitor additionally gives FLEXO® FR Plus a flame resistance rating of VW-1.

- **Specialized Lightweight Resin Coating**
- **Fray-Resistant Resin Coating Facilitates Easy Cutting w/Scissors**
- **Expands up to 150%**
- **Versatility of Installation**
- **Complies to HL2 According to Railway Standard DIN EN 45545-2**
- **Mil-202, FAR 25, FMVSS 302**
- **Melt Temp. 482°F**



Nominal Size	Part #	Expansion Range		Standard Spool Put-Ups		TB Available Colors	Lbs/ 100'
		Min.	Max.	Bulk Spool	Shop Spool		
1/8"	FRP0.13TB	1/16"	1/4"	1,000'	225'	TB	0.20
1/4"	FRP0.25TB	1/8"	7/16"	1,000'	200'	TB	0.30
3/8"	FRP0.38TB	3/16"	1/2"	500'	125'	TB	0.60
1/2"	FRP0.50TB	1/4"	3/4"	500'	100'	TB	0.80
3/4"	FRP0.75TB	1/2"	1 1/4"	250'	75'	TB	1.20
1 1/4"	FRP1.25TB	3/4"	1 3/4"	250'	50'	TB	1.60
1 1/2"	FRP1.50TB	1"	2 1/2"	250'	40'	TB	2.10
1 3/4"	FRP1.75TB	1 1/4"	2 3/4"	250'	30'	TB	2.90
2"	FRP2.00TB	1 3/4"	3 5/8"	200'	50'	TB	3.40
2 1/2"	FRP2.50TB	2"	3 7/8"	200'	50'	TB	3.50

