

2:1 Fabric Heatshrink Tubing

Shrinks to 1/2 its original diameter. Fabric heatshrink tubing, a unique mixture of polyolefin and polyester yarns, is the ideal way to form the only shrinkable fabric of its kind. The woven construction makes this product extremely flexible and resistant to trapping water, heat, and humidity. Provides outstanding abrasion, chafing, and cutting protection, even at high temperatures.

Shrinkflex fabric tubing is designed primarily to provide mechanical abrasion protection for components such as rubber hoses, plastic pipes, and harness wiring bundles. Also suitable for other applications, such as noise and rattle suppression.

- **Shrink Temp. 275°F**
- **Highly Flexible**
- **Resists Common Automotive Chemicals**
- **Easily Installs Over Connectors & Splices**
- **Halogen Free**

| Nominal Size | Part # | Unshrunk Diameter | Shrunk Diameter | Standard Spool Put-Ups | | Available Colors | Lbs/100' |
|--------------|-----------|-------------------|-----------------|------------------------|------------|------------------|----------|
| | | | | Bulk Spool | Shop Spool | | |
| 1/2" | H2F0.48BK | 12mm | 6mm | 100' | 25' | Black (BK) | 1.15 |
| 3/4" | H2F0.79BK | 20mm | 10mm | 100' | 25' | Black (BK) | 1.61 |
| 1 3/16" | H2F1.18BK | 30mm | 15mm | 100' | 25' | Black (BK) | 2.13 |
| 1 1/2" | H2F1.58BK | 40mm | 20mm | 100' | 25' | Black (BK) | 2.66 |
| 2" | H2F1.97BK | 50mm | 25mm | 100' | 25' | Black (BK) | 3.44 |
| 2 3/8" | H2F2.36BK | 60mm | 30mm | 100' | 25' | Black (BK) | 4.11 |
| 2 3/4" | H2F2.75BK | 70mm | 35mm | 100' | 25' | Black (BK) | 4.69 |



2:1 Diesel Resistant Heatshrink Tubing

Diesel resistant heatshrink tubing is the ideal way to create a tight, professional finish on any wire, hose, or cable management project. Once shrunk, the tubing will hold its reduced state even in elevated temperatures. H2D is resistant to aviation and diesel fuels, hydraulic fluids, and lubrication oils. It will protect wires, solder joints, terminals, connections, and components from most industrial fuels and abrasion.

| Nominal Size | Part # | Unshrunk Diameter | Shrunk Diameter | Standard Spool Put-Ups | | Available Colors | Lbs/100' |
|--------------|-----------|-------------------|-----------------|------------------------|------------|------------------|----------|
| | | | | Bulk Spool | Shop Spool | | |
| 1/8" | H2D0.13BK | 3.2mm | 1.6mm | 500' | 25' | Black (BK) | 0.70 |
| 3/16" | H2D0.19BK | 4.8mm | 2.4mm | 250' | 25' | Black (BK) | 1.00 |
| 1/4" | H2D0.25BK | 6.4mm | 3.2mm | 250' | 25' | Black (BK) | 1.20 |
| 3/8" | H2D0.38BK | 9.6mm | 4.8mm | 200' | 25' | Black (BK) | 1.75 |
| 1/2" | H2D0.50BK | 12.8mm | 6.4mm | 100' | 25' | Black (BK) | 2.75 |
| 3/4" | H2D0.75BK | 19.3mm | 9.5mm | 100' | 25' | Black (BK) | 4.75 |
| 1" | H2D1.00BK | 25.4mm | 12.7mm | 100' | 25' | Black (BK) | 8.80 |
| 1 1/4" | H2D1.25BK | 31.8mm | 15.9mm | 100' | 25' | Black (BK) | 12.60 |
| 1 1/2" | H2D1.50BK | 38.2mm | 19.1mm | 100' | 25' | Black (BK) | 12.20 |

- **Shrink Temp. 302°F**
- **Heavy Wall, Flexible Elastomer Polyolefin Tubing**
- **High Resistance to Aviation Fuels, Diesel Fuels, and Oils**

Contact your account representative for heatshrink cutting & printing services.

1 (833) SLEEVING
www.techflex.com