



SHRINKFLEX® 3:1 SHIELDING FLAME RETARDANT UL 224 · MEETS SPECIFICATION MIL-I-DTL-23053/5 EXCELLENT HIGH FREQUENCY EMI SHIELDING

3:1 Shielding heatshrink tubing is a unique combination of Polyolefin and conductive cloth, with a high frequency EMI shielding properties. This product, a flame retardant and fluid resistant tubing, is a perfect solution for protecting your wire & cable bundles.

SIZING CHART

Nominal Size	Part #	Unshrunk Diameter /mm	Shrunk Diameter /mm	Wall Thickness After	4 Feet Pcs. *Put-Ups		Available Colors	Lbs/ 10Pcs.
					M	L		
3/8"	H3C0.38BK	9.0	3.0	.031"	2	12	1	0.49
1/2"	H3C0.50BK	12.0	4.0	.033"	2	12	1	0.62
3/4"	H3C0.75BK	18.0	6.0	.039"	2	12	1	0.90
1"	H3C1.00BK	24.0	8.0	.048"	2	12	1	1.35
1 1/2"	H3C1.50BK	40.0	13.0	.050"	2	12	1	2.12
2"	H3C2.00BK	50.0	17.0	.059"	2	12	1	2.94

Put-Ups: "M" = Shop Spool and "L" = Bulk Spool

FEATURES

Material	Polyolefin
Grade	H3C
Wall Thickness After Shrinkage	.031"-.059"
Drawing Number	TF001H3C-WD
Cutting	Scissors

COLORS



Black (BK)

CERTIFICATIONS



HEATSHRINK TUBING

Technical Data Sheet



CHEMICAL RESISTANCE

Fluid Resistance	Excellent
------------------	-----------

FLAMMABILITY

Rating	Flame Retardant UL 224
--------	------------------------

SHIELDING EFFECTIVENESS (ASTM D-4935)



OPERATING TEMPERATURES

Shrinks	194°F / 90°C
Melt Point (ASTM D-2117)	392°F / 200°C
Maximum Continuous (Mil-I-23053)	275°F / 135°C
Minimum Continuous (Mil-I-23053)	-67°F / -55°C

PHYSICAL PROPERTIES


Wall Thickness After Shrinkage	.031"-.059"
Flammability Rating	UL 224
Recommended Cutting	Scissors
Colors	1
Flexibility	Medium
Break Strength After Shrinkage	1,500
Dielectric Strength (volt/mil)	500

HOW-TO

Measure the Shrinkflex® tubing to length and cut with a scissor. The thickness of your bundle, as well as the desired final appearance, will determine the length of the tubing you cut. Generally, a piece 1½" - 2" long will accommodate almost any need. Single wires, or smaller bundles, require shorter pieces.

Slip the Shrinkflex® tubing over the bundle and position it so that both the sleeved and unsleeved portions are sufficiently covered. Notice the small pieces of tubing installed on single wires as part of a color coding system. If your project requires multiple operations, always work up from the smallest to the largest bundle.

Gently apply heat to Shrinkflex® tubing from a heat gun, hair dryer or torch with an appropriate attachment. Keep the heat source far enough away so that hot metal or direct flame does not come in contact with the tubing, wires or sleeving. Move the heat around the bundle to prevent damaging the sleeving and to ensure that all areas of the tubing have been shrunk. Once cooled, your installation is complete.



www.TECHFLEX.com

104 Demarest Road • Sparta, NJ 07871 • 1 (833) SLEEVEING • (973) 300-9242 • fax: (973) 300-9409

© 2023 Techflex® - Any unauthorized reproduction, in whole or part, in any medium whatsoever, without the express written permission of Techflex® is strictly forbidden. Techflex® product names and logos are registered trademarks of Techflex®, unless otherwise attributed. The contents and illustrations contained herein are believed to be reliable. Techflex® makes no warranties as to their accuracy or completeness and disclaims any liability in connection with their use. Techflex's® only obligations are those in standard terms of sale for these products and Techflex® will not be liable for any consequential or other damages arising due to misuse of these products or typographical errors or omissions. Users should make their own evaluation to determine the suitability of these products for their unique and specific applications.

01-01-23