

- Shrink Temp. 194°F
- Flame Retardant
- Versatile & Economical Termination Solution
- Resists Common Automotive Chemicals
- Easily Installs Over Connectors & Splices

## 4:1 Polyolefin Heatshrink Tubing

4:1 Shrinkflex heatshrink tubing is the most versatile of the heatshrink products. The high shrink ratio ensures that the tubing will slip over large connectors or plugs and still provide a tight, professional seal.

This high shrink ratio tubing shrinks 75% or more in the radial direction and 50% or less in the axial direction. Resistant to abrasion, chemicals, and oils, Shrinkflex tubing will ensure maximum protection while providing neat end terminations.

Nominal Size	Part #	Unshrunk Diameter	Shrunk Diameter	Standard Spool Put-Ups		Available Colors	Lbs/ 100'
				Bulk Spool	Shop Spool		
1/2"	H4N0.50BK	12.0mm	3.0mm	200'	25'	Black (BK)	1.17
3/4"	H4N0.75BK	19.0mm	4.5mm	100'	25'	Black (BK)	2.75
1"	H4N1.00BK	25.4mm	7.0mm	100'	25'	Black (BK)	3.25
1 1/4"	H4N1.25BK	32.0mm	8.0mm	100'	25'	Black (BK)	4.00
1 1/2"	H4N1.50BK	38.0mm	9.5mm	100'	25'	Black (BK)	4.25



## Ultra Clear 2:1 PVC Heatshrink Tubing

Shrinks to 1/2 its original diameter. Ultra clear PVC heatshrink tubing is ideal for applications where complete transparency is required.

PVC is perfect for protecting exposed wires and cables on motorcycles and custom automobiles. Resists gasoline, oil, and common chemicals; provides protection from abrasion and severe environments.

Nominal Size	Part #	Unshrunk Diameter	Shrunk Diameter	Standard Spool Put-Ups		Available Colors	Lbs/ 100'
				Bulk Spool	Shop Spool		
1/16"	H2P0.06	1.6mm	0.8mm	1,000'	100'	CL & BK	0.20
1/4"	H2P0.25	6.4mm	3.2mm	250'	25'	CL & BK	0.60
5/16"	H2P0.31	8.0mm	4.0mm	250'	25'	CL & BK	0.70
3/8"	H2P0.38	9.5mm	4.8mm	250'	25'	CL & BK	0.80
1/2"	H2P0.50	12.7mm	6.4mm	250'	25'	CL & BK	1.10
5/8"	H2P0.63	15.9mm	7.9mm	250'	25'	CL & BK	1.16
3/4"	H2P0.75	19.1mm	9.5mm	250'	25'	CL & BK	1.90
1"	H2P1.00	25.4mm	12.7mm	250'	25'	CL & BK	3.00
1 1/2"	H2P1.50	38.1mm	19.1mm	100'	25'	CL & BK	5.30
2"	H2P2.00	50.8mm	25.4mm	100'	25'	CL & BK	8.02
2 1/2"	H2P2.50CL	63.5mm	31.8mm	100'	25'	Clear CL	9.45
3"	H2P3.00CL	76.2mm	38.1mm	50'	25'	Clear CL	18.00

Stays clear when shrunk.

1 (833) SLEEVING  
www.techflex.com

Contact your account representative for heatshrink cutting & printing services.